

Technical Specifications

Cold Press Rough Textured Natural White 315gsm

Fine Art Range IFA 13

Product Description

Rough textured matte, alpha cellulose, archival quality digital fine art paper with aqueous pigment and dye inkjet compatible coating.

Features

- · Natural White
- · Archival acid and lignin free
- Instant dry
- · Aqueous pigment and dye ink compatible
- Excellent colour gamut
- Exceptional d-max

Applications

- Fine art and photographic open and limited edition prints
- Fine art and fine photographic reproduction and restoration
- · Art and photo portfolios
- · Photo albums, memory books and wedding albums
- Greeting cards and postcards

Basic Weight (gsm)	315	
Paper Thickness (Microns)	495 Paper Thickness (Inches) 0.019	
Base Material	Alpha Cellulose	
Coating Type	Matte	
Surface Texture	Rough Textured 'Watercolour Paper'	
Whiteness (CIE)	69	
Brightness (TAPPI)	85	
OBA Content	No	
рН	7.5-9.5	
Recyclable	Yes	
Print Settings*	MK Ink, Fine Art Textured or Archival Matte Paper Settings are recommended as a starting point	
Notes		

*Generic ICC Profiles for selected printer models are available from the Innova Art website.

Sheets	A4, A3, A3+, A2, 8.5x11", 11x17", 13x19", 17x22"
Rolls (15m Length)	60", 44", 36", 24", 17"

Additional Sizes are available on request, subject to order quantity.

Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

Conditions of Use

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.

